





	System Power	8.4W					
2	CRI	>90Ra					
tio	ССТ	2700K	3000K				
na	LED Lumen	520lm	550lm				
orr	LED Efficacy	84lm/W	89lm/W				
Inf	LOR	>8	>85%				
lct	Driver	350mA Non-Dimmable or Dimmable Driver (included)					
Product Information	Reflector	38°					
			uded				



System includes: fixture, driver and quick connector



Quick connector (included)





Two light frame (not included) Cutout Size 80\*155mm


est	Article No.	Description				
ŋpŝ	2.01.0720	Two light ceiling frame for LED spot Smooth 8.4W Aluminium	- 1-10v or DALI dimmable driver available on request			
Re	2.01.0721	Two light ceiling frame for LED spot Smooth 8.4W White				
ō	For two light Smooth 8.4W versatile, please order 2* single lights and 1* two light ceiling frame.					



## Smooth CRI90 8.4W 3000K







Article No.	Product Name	Color	LED Lumen	сст	CRI	Cooling	LED Power	Reflector	Cutout Size
2.11.1666 / 2.11.16671	LED spot Smooth square 8.4W versatile	Aluminium	520lm	2700K	>90Ra	Passive	6W	38°	Ø 75mm
2.11.1669 / 2.11.1670 <sup>1</sup>	LED spot Smooth square 8.4W versatile	Sandy White	520lm	2700K	>90Ra	Passive	6W	38°	Ø 75mm
2.11.1672 / 2.11.1673 <sup>1</sup>	LED spot Smooth square 8.4W versatile	Aluminium	550lm	3000K	>90Ra	Passive	6W	38°	Ø 75mm
2.11.1675 / 2.11.1676 <sup>1</sup>	LED spot Smooth square 8.4W versatile	Sandy White	550lm	3000K	>90Ra	Passive	6W	38°	Ø 75mm
<sup>1</sup> Article number with <sup>1</sup> indicates dimmable driver is included.									

Article number with ' indicates dimmable driver is included