

Vela


ROUND FIXED



Product information

| | |
|-----------------|--|
| System Power | 12w |
| CRI | >90Ra |
| CCT | 2700K 3000K 4000K |
| System Lumen | 688lm 749lm 865lm |
| System Efficacy | 56lm/W 61lm/W 70lm/W |
| LOR | Up to 81% |
| Driver | 500mA Non-Dimmable or Dimmable Driver (included) |
| IP | IP44 |

Dimensions



Vela Round Fixed

| Article No. | Product Name | Color | CCT | CRI | System Lumen | System Power | Reflector | Cutout size |
|------------------------|--------------|-------|-------|-------|--------------|--------------|-----------|-------------|
| 2.11.1957 / 2.11.1958* | Vela | Grey | 2700K | >90Ra | 688lm | 12W | 38° | Ø 75mm |
| 2.11.1963 / 2.11.1964* | Vela | White | 2700K | >90Ra | 688lm | 12W | 38° | Ø 75mm |
| 2.11.1969 / 2.11.1970* | Vela | Black | 2700K | >90Ra | 688lm | 12W | 38° | Ø 75mm |
| 2.11.1959 / 2.11.1960* | Vela | Grey | 3000K | >90Ra | 749lm | 12W | 38° | Ø 75mm |
| 2.11.1965 / 2.11.1966* | Vela | White | 3000K | >90Ra | 749lm | 12W | 38° | Ø 75mm |
| 2.11.1971 / 2.11.1972* | Vela | Black | 3000K | >90Ra | 749lm | 12W | 38° | Ø 75mm |
| 2.11.1961 / 2.11.1962* | Vela | Grey | 4000K | >90Ra | 865lm | 12W | 38° | Ø 75mm |
| 2.11.1967 / 2.11.1968* | Vela | White | 4000K | >90Ra | 865lm | 12W | 38° | Ø 75mm |
| 2.11.1973 / 2.11.1974* | Vela | Black | 4000K | >90Ra | 865lm | 12W | 38° | Ø 75mm |

Article No. with * indicates that the luminaire is DALI Dimmable.